

## Cable Description:

- 1F Mini Flat Drop Toneable- 2.7 x 6.7MM SM G.657.A1 (24AWG conductor)
- 1F Mini Flat Drop Dielectric- 2.7 x 6.7MM SM G.657.A1

## Features:

- Re-sealable packaging for convenient access and secure storage
- Reinforced grommet exit ensures durable, controlled cable payout
- Engineered design minimizes cable spring-back and uncontrolled uncoiling

Unit Length	Reel Size	Pull-Out Type (Reel-in-Box)
		Box Size
1,000 ft	12.01x3.94x5.71in	330*190*335mm
2,000 ft	305*100*300mm	330*345*335m
3,000 ft	430*203*311mm	460*365*465mm
5,000 ft	430*143*311mm	

## Performance:

- Tensile Strength: 1350N
- Crush Strength: 1000N/10cm
- Impact: 2.94N.m
  - 2 impacts
  - 3 point (Interval 150mm)
- Bend Radius: 20 x Cable O.D (Single-helix)
- Operating Temperature: -20C to +70C

## Reel-in-Box

### Amphenol Custom Cable's Reel-in-Box Solution:

Delivers a compact, efficient packaging option for field installation. Designed for quick transport, easy storage, and smooth cable payout, it streamlines deployment across a wide range of installation environments.

**Engineered for faster, more efficient, and more reliable installations.**



CustomCable.com - (800) 446-2232



LEARN MORE